LNR SOP 500

Page: 1 of 4

Last Modified: 8/31/2015

eci. Opei	auny u	e Chainsaw	Approved: Patrick Bohlen
PROCEDURE:		Operating the Chains	aw
INTENDED AUDIENCE:		LNR personnel with access to Chainsaws	
PURPOSE:		To train LNR person to operate chainsaw to successfully remove tree and vegetative debris without damage to personnel or infrastructure.	
I. Knowle	edge		
	a. Read operators equipment manual (OEM).		
	b. Operation	tor should understand kickback, how it happens, and	
	how t	o prevent it.	
	c. Opera	or should be familiar with safety and the general operation	
	of the	chain saw before attempting	g its use.
II. Safety			
a. At a m		inimum, follow the safety requirements listed in the OEM	
	for the	e equipment being used. It is the employee's responsibility	
	to det	ermine if added Personal Pro	otective Equipment is needed
	and th	erefore must consult with th	eir Supervisor prior to starting
	the ta	sk.	
		nal Protective Equipment (P)	PE) includes:
		Helmet	
		Hearing protection	
	iii.		
		Steel toe boots	
		Safety goggles	
		Work rated chainsaw chaps	
		Long pants and shirt	
	-	Derating Chainsaw	1 1 1 1 1
		or proper chain grease levels	
b.		or damaged or worn saw teet hanics for filing).	th, file to a point if necessary (or

LNR SOP 500

Page: 2 of 4

Last Modified: 8/31/2015

Subject: Operating the Chainsaw

Approved: Patrick Bohlen

WARNING: Never operate a chainsaw with loose clothing

WARNING: Never operate a chainsaw alone.

c. Be sure the chain is tensioned properly before starting engine and that the chain brake is functioning.

Note: If at any time equipment is not working properly, attach a 3x6 tag from the LNR shop area on hand held equipment with a short explanation of the problem. When repair is complete, chainsaw will be staged outside the LNR shop door for pick up.

d. If equipment is operating properly proceed to work area.

IV. Steps for Operating Chainsaw

- a. Apply the chainsaw brake when starting engine.
- b. Wipe dirt and dust away from filler caps before adding mixed gas.
- c. Check fluids (mixed gas and bar chain oil) and add as needed.
- d. Prime chainsaw.

WARNING: Always check overhead for power lines or obstructions.

WARNING: Always check up the tree for loose or hanging branches (widow makers) that can fall and impact the sawyer.

e. Set the chain saw on the ground and turn on the choke.

CAUTION: Be sure the chainsaw brake is engaged.

- f. Pull start cord until you hear ignition.
- g. Turn off the choke once ignition is engaged.
- h. Re-pull starter chord and begin sawing operations.

LNR SOP 500

Page: 3 of 4

Last Modified: 8/31/2015

Subject: Operating the Chainsaw

Approved: Patrick Bohlen

WARNING: Never operate a chainsaw over chest height.

WARNING: Keep a wide stance to keep balanced, and always use two (2) hands when operating the chain saw.

i. Use teeth at base of chainsaw to anchor as you cut.

WARNING: Understand kickback, how it happens and how to prevent it.

j. When felling a tree, saw a 45 degree angle notch halfway through the tree.

WARNING: When felling a tree, ensure two routes of escape are available at 45 degree angles to where the tree is meant to fall.

k. Use teeth at base of chainsaw to anchor as you cut.

WARNING: When performing back cut, place the chain saw at least two inches (2") above the crux of the 45 degree notch. Always keep an eye on the tree when performing cuts, and be wary of unplanned fall directions.

1. Perform the back cut by sawing on the opposite side of the tree.

Note: Always attempt to fell tree in the direction it naturally leans unless using a wedge.

CAUTION: When limbing large branches, always perform a three (3) state cut to prevent tearing unintended tissue.

m. Turn off chainsaw after operation is completed.

LNR SOP 500

Page: 4 of 4

Last Modified: 8/31/2015

Subject: Operating the Chainsaw	Approved: Patrick Bohlen

V. After Operation Steps for Chainsaw

- a. Collect any generated debris and dispose of per supervisor's instructions.
- b. Secure the chainsaw in staging area for next use.